# Where do you need Spare Air today?





### Spare Air Model 300 (regular air and Nitrox)

3 cu ft / 85 liters Cylinder Capacity: Length: 13" / 33 cm Diameter: 2.5" / 6.4 cm Service Pressure: 3000 psi / 207 bar 2.2 lb. / 1 kg Weight:

Surface Breaths\*:

# Spare Air Model 600 (regular air and Nitrox)

Cylinder Capacity: 6 cu ft / 170 liters 13.3" / 34 cm Length: 3.2" / 8.2 cm Diameter: 3000 psi / 207 bar Service Pressure: 3.4 lb. / 1.5 kg Weight:

Surface Breaths\*:

The first Spare Air was specifically designed for SCUBA Diving out-of-air emergencies. Since 1979, we have provided the best selling redundant air supply in the world.

ameri (#



## Xtreme Model 170PKX

Cylinder Capacity: 1.7 cu ft / 48 liters Lenath: 8.75" / 22 cm Diameter: 2.25" / 5.7 cm Service Pressure: 3000 psi / 207 bar 1.5 lb. / .7 kg Weight: Surface Breaths\*: 32

The Xtreme Sport is designed to allow athletes more time to self-rescue from the dangers of extreme sports like tow-in surfing and kayaking.

### Xtreme Model 600PKX

Cylinder Capacity: 6 cu ft / 170 liters Length: 14" / 36 cm 3.2" / 8.2 cm Diameter: Service Pressure: 3000 psi / 207 bar Weight: 5 lb. / 2.3 kg Surface Air Duration: Up to 20 minutes

The Xtreme 6 is a complete mini dive and snorkel system. Comes fully assembled, ready to strap on to your waist and jump in the water.

**IEE** 

\* based on 1.5 liter breath size



Cylinder Capacity: 2 cu ft / 58 liters 9.75" / 25 cm Lenath: Diameter: 2.5" / 6.4 cm Service Pressure: 3000 psi / 207 bar Weight: 2.3 lb. / 1 kg

Surface Breaths\*: 38

Hose Length: 20" or 27"

### **HEED 3 175 Series**

Cylinder Capacity: 2 cu ft / 58 liters 9.5" / 24 cm Length: Diameter: 2.5" / 6.4 cm Service Pressure: 3000 psi / 207 bar Weight: 1.8 lb. / .8 kg

Surface Breaths\*: 38

**HEED 3 300 Series** 

Cylinder Capacity: 3 cu ft / 85 liters Lenath: 13" / 33 cm Diameter: 2.5" / 6.4 cm Service Pressure: 3000 psi / 207 bar 2.2 lb. / 1 kg Weight:

Surface Breaths\*: 57

The HEED 3 was designed for the US military as an emergency egress device during waterborne crashes. The custom MOLLE holster mounts easily to a modular vest, aircraft or vehicle.



# **Spare Air Industrial & Escape**

Cylinder Capacity: 3 cu ft / 85 liters Lenath: 13" / 33 cm Diameter: 2.5" / 6.4 cm Service Pressure: 3000 psi / 207 bar Weight: 2.2 lb. / 1 kg

Surface Breaths\*:

Spare Air is used as a safety device for out-of-air emergencies and toxic air/fires in the workplace or at home.



Cylinder Capacity: 3 cu ft / 85 liters Length: 14" / 35 cm Diameter: 2.5" / 6.4 cm Service Pressure: 3000 psi / 207 bar Weight: 2.5 lb. / 1.1 kg

Surface Breaths\*: 57

HEED 3 - SWBA is the first to market type-approved device under the global Good Practice Guideline - Swiftwater Breathing Apparatus.